



KONICA MINOLTA

Giving Shape to Ideas



100 ppm print/copy output – up to 6,000 impressions per hour  
2,250,000-Page monthly duty cycle meets high-volume demands  
1200 x 1200 dpi resolution with advanced LED technology for smooth halftones and sharp text  
Standard color dual scanning at up to 180 originals per minute  
Built-in print controller, flexible scanning to Email, FTP, SMB, HDD, USB and TWAIN scanning  
Job ticket and page editing from 15" touch-screen display for easy on-board press control  
Job Centro and Hot Folder capabilities for job management and workflow  
9,000-Sheet maximum paper capacity for long unattended runs  
Media sizes up to 12" x 18" and weights up to 350 gsm, duplex capability up to 300 gsm  
Reliable air-assisted paper-feeding for worry-free printing  
All-in-one staple finisher with kits for saddle-stitching, hole-punching and post-insertion  
Simitri® HD toner with Biomass fuses at lower temperatures  
Optional bypass tray and output tray  
EPEAT Gold-certified

## bizhub PRO 1100

MONOCHROME DIGITAL PRODUCTION PRINTER / COPIER / SCANNER

press



press



## bizhub PRO 1100

MONOCHROME DIGITAL PRODUCTION PRINTER / COPIER / SCANNER

**Description**

**bizhub PRO 1100 Overview**

The bizhub PRO 1100 delivers real value to any print production environment – with high-speed 100 ppm B&W output, high paper and toner capacity, standard built-in print controller and compact footprint to save space on your production floor. Dedicated to central in-house printing facilities and external print-for-pay services - this device provides sturdy construction, high performance and numerous inline finishing options teamed up with advanced technology for enhanced B&W print quality. Be more productive with high-performance color scanning capability with dual scanning ADF in combination with the powerful print engine.

**System specifications**

<b>Type</b>	Console
<b>Resolution</b>	1,200 x 1,200 dpi / 8-bit 256
<b>Original type</b>	Sheets, Books, Objects
<b>Max. Original size</b>	11" x 17"
<b>Memory capacity</b>	DIMM: 8 GB / HDD: 1TB
<b>Paper size</b>	<b>Standard:</b> 12" x 18", 11" x 17", 8.5" x 11", 8.5" x 14", 9" x 11", 8" x 13", 5.5" x 8.5" <b>Custom:</b> 7.17" x 5.5" to 12.76 x 18.23", 8.5" x 11" tab paper
<b>Image loss</b>	<b>Top edge:</b> Max. 3 mm or less <b>Right / Left / Bottom edge:</b> Max. 2 mm or less
<b>Warm-up time</b>	390 sec. or less
<b>First copy out time</b>	3.4 sec. or less
<b>Copy / print speed (Letter)</b>	100 ppm
<b>Copy magnification</b>	<b>Fixed same magnification:</b> 1:1 ± 0.5% or less <b>Scaling up:</b> 1:1.154 / 1.224 / 1.414 / 2.000 <b>Scaling down:</b> 1:0.866 / 0.816 / 0.707 / 0.500 <b>Preset:</b> 3 types <b>Zoom:</b> 25 to 400% (in 0.1% increments)
<b>Paper capacity</b>	<b>Standard:</b> 1,500 sheets x 2 (80 gsm)
<b>Paper weight</b>	<b>Standard:</b> 40 to 300 gsm (Limitations to paper types apply) <b>Option:</b> 40 to 350 gsm (Only available for middle tray of PF-709)
<b>Multiple copy</b>	1 to 9,999 sheets
<b>Power requirements</b>	208 to 240 V, 60Hz, 16 A, Dedicated line
<b>Max. Power consumption</b>	3.6 kW or less (Main unit + PF-709 + FS-532)
<b>Dimensions (W) x (D) x (H)</b>	Main unit + ADF: 39" x 35.75" x 45.75" Including operation panel: 47.75" x 35.75" x 57.25"
<b>Weight</b>	749.5 lb (Main unit)
<b>Space requirements (W) x (D)</b>	Main unit + FS-532 + LU-411: 103-3/4" x 81-1/4"

**Printer specifications**

<b>Type</b>	Embedded
<b>CPU</b>	Pentium G3420 3.2 GHz
<b>Memory</b>	2 GB
<b>HDD</b>	1 TB 3.5 inch SATA
<b>Print speed</b>	100 ppm
<b>Print resolution</b>	1,200 x 1,200dpi, 600 x 600dpi
<b>PDL</b>	PCL5e/6, PostScript3 (3020), PDF Ver1.7, TIFF Ver. 6 Emulation, PPML (Ver2.2)
<b>Protocol</b>	TCP/IP (LPR, RAW socket), IPX/SPX (NDS, Bindery), NetBEUI, IPP, AppleTalk, WSD, Bonjour, SMB
<b>Compatibility</b>	<b>PCL:</b> Windows Vista* / 7* / 8* / 8.1* / Windows Server 2008* / 2008 R2 2012 / 2012 R2 <b>PS:</b> Windows Vista* / 7* / 8* / 8.1* Windows Server 2008* / 2008 R2 2012 / 2012 R2 / <b>Mac OS X:</b> 10.6 / 10.7 / 10.8 / 10.9 / 10.10
<b>Fonts</b>	<b>PCL:</b> 80 fonts / <b>PS:</b> 136 fonts
<b>Interface</b>	10Base-T/100Base-TX/1000Base-T, USB 3.0 host, USB 2.0 device

\*Supports 32-bit (x86) or 64-bit (x64) environment.

**Scanning specifications**

<b>Type</b>	Full-Color Scanner
<b>Scanning speed</b>	<b>Simplex:</b> 90 opm (Color/B&W / Letter @ 400 dpi) <b>Duplex:</b> 180 opm
<b>Scanning size</b>	11" x 17"
<b>Scanning resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi
<b>Protocol</b>	TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)
<b>Compatibility</b>	Windows Vista* / 7* / 8* / 8.1*
<b>Interface</b>	Ethernet 10Base-T/100Base-TX/1000Base-T
<b>Output format</b>	PDF, TIFF, Encrypted PDF, XPS, Compact PDF, JPEG

\*Supports 32-bit (x86) or 64-bit (x64) environment.

**Dual scan document feeder (standard)**

<b>Type</b>	Single pass simultaneous duplex system
<b>Original size</b>	11" x 17"
<b>Paper weight</b>	Simplex 35 to 210 gsm / Duplex 50 to 210 gsm
<b>Paper capacity (80 gsm)</b>	Max. 150 sheets
<b>Dimensions (W) x (D) x (H)</b>	24-1/4" x 22-3/4" x 5-1/2"
<b>Weight</b>	Approx. 39.75 lb

**Options**

<b>AU-205H IC Card reader</b>	Various IC card certification device
<b>FS-532 Stapling unit</b>	All-in-One 100-sheet staple finisher / 4,200 sheets max. output
<b>GP-501 Multi (GBC) punching unit</b>	8.5" x 11" GBC Multi-puncher (7 optional user replaceable dies)
<b>GP-502 Auto ring binding unit</b>	8.5" x 11" In-line GBC ring binding unit
<b>LU-411 Large capacity tray</b>	Up to 4,500 sheets / 8.5" x 11" / 40-300 gsm
<b>LU-412 Large capacity tray</b>	Up to 4,000 sheets / 8.5" x 11" to 12" x 18" / 40-300 gsm
<b>MB-507 Multi bypass tray</b>	Up to 250 sheets / 5.5" x 8.5" to 12" x 18" / 40-300 gsm
<b>OT-507 Output tray</b>	Up to 150 sheets / 5.5" x 8.5" to 12" x 18" / 62-300 gsm
<b>PF-709 Air assist paper feed unit</b>	Up to 6,000-sheets total / 5.5" x 8.5" to 12" x 18" / 40-350 gsm
<b>PI-502 Post inserter</b>	Cover insertion, post finishing for FS-532
<b>PK-522 Punch kit</b>	2/3-hole punching, autoswitching for FS-532
<b>RH-101 / HD-523 Hard disk kit</b>	Removable HDD Kit
<b>SD-510 Saddle stitch kit</b>	Saddle-stitch/folding kit for FS-532 / 25-sheet booklets with Half-fold and Tri-fold
<b>ZU-608 Z-fold unit</b>	Z-fold unit for for FS-532 / 11"x17" prints / 2/3-hole punching



KONICA MINOLTA

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, bizhub PRESS, PageScope, Simitri, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.  
100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: 1100SS  
1/16 - S